

Full vision goggles with exceptional wearer comfort. Anti-Scratch and Anti-Fog.

Twin materials combination (hard/soft) reduces pressure and enhances user safety.



**900
161**

CE EN 166 : 2001 EN 170

Main Applications

- **Industry**
- **Building construction**
- **Agriculture**
- **Chemical environment**




Main Features

- **Large field of vision**
- **Comfortable with twin material combination**
- **Perfect fit**
- **Suitable for use with respiratory masks and prescription spectacles**

Engraved Markings

- **Clear : 2C-1.2 RSG 1 9 BT***
- **Frame: CE EN 166 3 4 9 BT***

*Complementary test in extreme conditions -5°C till +55°C.

Reference	900 161
Frame Material	PC + PPR
Lens Material	PC polycarbonate
Lens Base Curve (mm)	5.5
Lens Thickness (mm)	2.2
Anti-Scratch	 anti scratch
Anti-Fog	 anti fog
UV 380	-
Weight (g)	86
Soft Nose Pad	 soft nose pad
Soft Temple Tips	-
Temple Pivot System	-
Vented	-
Suitable for use with prescription glasses	X
Air/watertight	-
Lens Markings	2C-1.2 RSG 1 9 BT*
Frame Markings	CE EN 166 3 4 9 BT* RSG
Quantity per box	4
Quantity per full carton	120