

T-AirLine 1000M

614050

The T-AirLine Series headtops offer lightweight and comfortable protection in many industrial applications. The T-AirLine range is manufactured to the latest respiratory regulations. It provides protection for eye, face, neck, and shoulders and is ideal in environments where the highest possible levels of protection are required.

CE EN 14594: 2005 Class 4A

Main Applications

- Pharmaceutical
- Paint spraying
- Light chemical aerosols
- Liquid particles
- Powder and dust environments

Main Features

- Respiratory protection
- Eye, face, neck and shoulders protection
- Replaceable hood.
- PETG visor
- Adjustable head harness
- Neck seal.
- Strong and flexible PE breathing hose.
- Equipped with exhalation valve.
- Unique low airflow indicator.
- Comfortable easy to adjust airflow
- Easy donning and doffing.
- Easy to maintain.

Spare parts

- 660217 Headgear with Airflow indicator
- 660252 Hood Microporous
- 661368 T-AirLine regulator with belt
- 660048 Charcoal filter
- 661370 Hose with Bayonet connectors
- 661470 Sweatband



**614
050**

Reference	614050
EN Standard	EN14594:2005
Class	4A
NPF	2000
Working pressure	3 – 6 bar (Max 10)
Airflow	180 – 350 Adjustable
Weight of regulator incl. hose (g)	330
Noise level	59-80dB depending on airflow
Temperature range (°C)	-10 - + 50
Hood Material	65 gsm Microporous film laminate (limit use)
Abrasion resistance (cycles)	< 100 (EN530)
Puncture resistance (N)	6,2 (EN862)
Bursting strength (KN/M ²)	50,9 (ISO2960)
Flex Cracking resistance (cycles)	>15K<40K (ISO7854)
Trapezoidal tear strength (N)	40,6/16,7 (ASI 9073)
Seam strength (N)	95,64 (EN5082)
Protection from reduced spray of liquid chemicals	Yes (EN13034:2005)
Protection from hazardous dry particles	Yes (EN13982:2004)
Liquid chemical protection	Yes (EN14605:2005)
Antistatic requirements	Yes (EN1149-1:2005)
Protection from radiation contaminated particulates	Yes (EN1073:2002)
Protection against infective agents	Yes (EN14126:2003)
Visor material	PETG
Visor strength	EN166 FT
Weight of headtop (g)	340
Quantity per box	1