





Headtops and hood options

Headtops and hood options

As part of our continuous product development, RSG is introducing a range of T-AirLine headtops for use with the new T-AirLine Airflow Regulator.





T-AIR 1000 M Part # 614050

- · For pharmaceutical, paint spraying or light chemical applications
- Hood made of Microporous film laminate with overpressure valve
- Includes RSG unique airflow indicator for low flow warning
- Easy adjustable head harness with ratchet Chemical resistant PETG visor
- Comfortable SMS neck seal
- · Includes RSG unique airflow indicator for low flow warning



T-AIR 1000 CHEM1 Part # 614051

- Provides good protection in waste disposal and chemical spill applications
- Hood made of HDPE barrier film laminate with overpressure valve
- Includes RSG unique airflow indicator for low flow warning
- Easy adjustable and reusable head harness with ratchet
- · Chemical resistant PETG visor Includes RSG unique airflow indicator for low flow warning
- Comfortable SMS neck seal



T-AIR 1000 CHEM3 Part # 614052

- petrochemical environments and hazardous waste disposal
- composite material with EVOH film barrier with exhalation valve
- Includes RSG unique airflow indicator for low flow warning
- Easy adjustable and reusable head harness with ratchet
- Chemical resistant PETG visor
- Comfortable SMS neck seal

EN14594 CLASS 4A

NPF 2000



T-AIRVISOR Part # 614100

- For grinding, paint spraying, pharmaceutical or light chemical handling
- Large viewing area, chemical and mechanical resistant visor
- Easy removal disposable visor system
- Possibility to flip up visor
- Comfortable elastic cotton face seal
- Includes RSG unique airflow indicator for low flow warning
- Easy adjustable head harness with ratchet

EN14594 CLASS 3BA **NPF 500**



Grinding / Welding

EN14594 CLASS 3B








- Hood made of Multi-layer

EN14594 CLASS 3B NPF 500



Paint spraying





aint Spraying



NPF 2000

EN14594 CLASS 4A



AIRLINE FILTER UNIT

Part # 600161 / 600162 / 600163 / 600164

- Breathing Air according EN12021:1999 offering clean, particle and oil free air
- Wall or floor mounted to suit 2 and 4 users
- 2 stage high dirt holding capacity 0.01 micron rated filter to remove particles and oil aerosol to 0.003 mg/m3
- Activated carbon filter to remove odours and vapours



The headtops are approved to EN14594:2005 Class 3B/4A and provide protection for eye, face, neck and shoulders. The T-AirLine series headtops offer lightweight and comfortable protection in many industrial applications. The range is manufactured to the latest respiratory regulations and provides protection for eye, face, neck and shoulders.



AIRLINE AIRWELD Part # 614260

- · Respiratory (EN14594) and eye protection (EN175B)
- · High quality ADF lens with 4 sensors, 9-13 variable for welding / grinding, optical class 1/2/1/1
- Easy adjustable head harness with ratchet
- Strong and flexible PE breathing hose
- · Comfortable easy to adjust airflow



AIRLINE AIRWELD Part # 614200 / 614201

- Respiratory (EN14594) and eye protection (EN175B)
- The T-AirWeld 500 can be equipped either with a fixed shade welding lens flip up
- Optional ADF lens with 2 sensors, 9-13 adjustable for welding / grinding, optical class 1/3/1/2
- Viewing area of 96 x 42 mm
- · Adjustable head harness with ratchet
- Strong and flexible PE breathing hose
- Comfortable, easy to adjust airflow regulator

NPF 500

Grinding / Welding

T-AILINE REGULATOR

Part # 661368


- Slim, safe and simple to operate
- · Precisely adjustable airflow (between 180-350 litres)
- Supplied with in-line charcoal filter, for taste and odour removal for improved user comfort and performance
- CEJN nipple, HDPE breathing hose. 40mm black PE belt
- EN approved with all RSG T-AirLine hoods according EN14594 class 3B/4A



Part # 661250 / 661252 / 661253

- Tested and approved with
- T-AirLine Filter Units, Regulators and all T-AirLine headtops
- All hoses fulfil the test procedures of the EN14593 & EN14594:2005
- Fitted with CEJN double action safety coupling and nipple for ease of use and safe (dis)connection
- Range of Light duty PVC plastic hoses, 10 and 20 meter and Heavy duty anti-static, heat resistant and flame retardant chemical resistant rubber hoses, 10, 20 and 30 meter
- Flexible spiral PU hoses in 2, 4, 6 and 8 meters











RSG Safety BV

Marinus Dammeweg 38 5928 PW VENLO The Netherlands

T +31(0) 854870395 sales@rsgsafety.com

www.rsgsafety.com

